

L109-000-DV**LUMININE DUAL VOLTAGE WORKLAMP**

Read these instructions before commencing installation and use. Pass this leaflet to end user.

 Safety Information

- To ensure safe installation and use this product should be used only in accordance with the instructions and should not be modified. Modification may invalidate product approvals.
- It is the responsibility of the installer to ensure safe installation of this product in accordance with the applicable national regulations.
- If you have any doubts at all as to the installation or use of this product, consult a competent person.
- To avoid risk of electric shock disconnect electrical supply before installation.
- Ensure that the supply voltage is compatible with that marked on the product rating label.
- Luminine worklamp is not to be operated whilst vehicle is in motion.

Thank you for purchasing the Luminine worklamp, it features nine powerful LED's that produce a flood beam light output. The luminine worklamp is manufactured from a cast aluminium alloy housing and High impact shatterproof lens that give this worklamp heavy duty durability for applications.

ITEM DESCRIPTION	QUANTITY
LUMININE WORKLAMP	1
FIXING BRACKET KIT	1
FITTING INSTRUCTIONS	1

Design Features:

- Nine powerful LED's.
- LED Lifetime: 30000 hours.
- Flood beam.
- Housing body: aluminium alloy.
- High Impact shatterproof lens.
- Waterproof rated to IP67.
- Cooling fins to the rear of lamp to regulate operating temperature.

Specification:

- Operating voltage: 10 - 30V.
- Current consumption: 2.25A @ 12V.
1.125A @ 24V.
- Dimensions: W 116mm.
H 135mm.
D 43mm.
- Approvals: 2004/108/EC
- LED power: 27W.
- Output In lumen 1800 lm.

Premier Hazard Ltd., YO16 4SJ, <http://www.premierhazard.co.uk>,

Tel.: +44(0)113 239 1111, E-Mail: info@premierhazard.co.uk



INSTALLATION INSTRUCTIONS:

- Black cable - Earth
- White cable - +12VDC
- Only use cables and fixing kits as supplied with this kit.
- Ensure worklamp is fitted securely in locations that would not cause vehicle operation to become hazardous.
- Avoid routing cables adjacent to high heat sources such as, engine block, exhaust.
- Take care not to trap or abrade cables.
- Protect cables from sharp metal edges.

Premier Hazard Ltd., YO16 4SJ, <http://www.premierhazard.co.uk>,

Tel.: +44(0)113 239 1111, E-Mail: info@premierhazard.co.uk

© 2010 Premier Hazard Ltd. A member of the Public Safety Equipment group of companies.
A member of the [Public Safety Equipment \(PSE\)](#) group of companies.

D00233-1-A REL 40093

**EC Declaration of Conformity**

We, the undersigned,

Manufacturer	PREMIER HAZARD LTD
Address	BESSINGBY INDUSTRIAL ESTATE
	BRIDLINGTON
	YO16 4SJ
Country	UNITED KINGDOM
Phone Number	0044 (0)113 2391111
Email	info@premierhazard.co.uk

Certify and declare under our sole responsibility that the following apparatus:

Description	LUMININE, DUAL VOLTAGE, WORKLAMP
	PREMIER HAZARD LTD
Part number	L109-000-DV

Description	LUMININE, DUAL VOLTAGE, WORKLAMP
	PREMIER HAZARD LTD
Part number	L109-001-DV

Description	LUMININE, DUAL VOLTAGE, WORKLAMP
	PREMIER HAZARD LTD
Part number	LL109-00W-DV

Conforms to the essential requirements of the EMC Directive 2004/108/EC, based on the following specifications applied:

EU Harmonised Standards:	EN61000-6-1: 2007
	EN61000-6-3: 2007
	EN55012: 2007

The products conform to the essential requirements and provisions of the EMC Directive.

Name and position of the person binding the manufacturer or his authorised representative	MALCOLM ROONEY OPERATIONS DIRECTOR
Address	PREMIER HAZARD LTD BESSINGBY INDUSTRIAL ESTATE BRIDLINGTON YO16 4SJ
Country	UNITED KINGDOM
Phone Number	0044 (0)1132391111
Email	malcolm.rooney@premierhazard.co.uk

Premier Hazard Ltd., YO16 4SJ, <http://www.premierhazard.co.uk>,

Tel.: +44(0)113 239 1111, E-Mail: info@premierhazard.co.uk

© 2010 Premier Hazard Ltd. A member of the Public Safety Equipment group of companies.
A member of the [Public Safety Equipment \(PSE\)](#) group of companies.

D00233-1-A REL 40093